


■ ILLUSTRATION IS TYPICAL ONLY OF GENERAL SERIES CONFIGURATION: FOR SPECIFIC CONFIGURATION, CALL JENSEN PRECAST.

MINIMUM EXCAVATION SIZE:  
6'-0" x 8'-6" x DEPTH REQUIRED.

- (A) TOP SECTION WT.= 3,524 Lbs.
- (B) 72" BOTTOM SECTION WT.= 13,629 Lbs.
- (C) 7" x 12" KNOCKOUT - ONE EACH END
- (D) 12" DIA. SUMP KNOCKOUT
- (E) FOR MANHOLE COVERS: SEE COVER AND NECKING SECTION.
- (F) 4" DIA. CAST-IN TERMINATORS

- DESIGN FOR H-20-44 BRIDGE LOADING.
- ASSEMBLY TO BE PLACED ON A 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.
- MINIMUM HEADROOM IS 6'-6". ADDITIONAL DEPTHS ARE AVAILABLE BY EXTENSION SECTIONS.

<b>4'-0" x 6'-6"</b> <b>x 6'-6" DEEP</b> <b>COMMUNICATIONS</b> <b>MANHOLE</b>		  <b>466 SERIES</b> COMMUNICATION
ORG. DWG. DATE <b>10-24-00</b>	REV. DWG. DATE	